

Enphase® Microinverters

# Enphase® M215



The **Enphase® M215 Microinverter** with integrated ground delivers increased energy harvest and reduces design and installation complexity with its all-AC approach. With the advanced M215, the DC circuit is isolated and insulated from ground, so **no Ground Electrode Conductor (GEC) is required for the microinverter**. This further simplifies installation, enhances safety, and saves on labor and materials costs.

The Enphase M215 integrates seamlessly with the Engage® Cable, the Envoy® Communications Gateway™, and Enlighten®, Enphase's monitoring and analysis software.

## PRODUCTIVE

- Maximizes energy production
- Minimizes impact of shading, dust, and debris
- No single point of system failure

## SIMPLE

- No GEC needed for microinverter
- No DC design or string calculation required
- Easy installation with Engage Cable

## RELIABLE

- More than 1 million hours of testing and millions of units shipped
- Industry-leading warranty, up to 25 years

INPUT DATA (DC)	M215-60-2LL-S22-IG / S23-IG / S24-IG	
Recommended input power (STC)	190 - 270 W	
Maximum input DC voltage	48 V	
Peak power tracking voltage	27 V - 39 V	
Operating range	16 V - 48 V	
Min/Max start voltage	22 V / 48 V	
Max DC short circuit current	15 A	
Max input current	10 A	
OUTPUT DATA (AC)	@208 VAC	@240 VAC
Peak output power	225 W	225 W
Rated (continuous) output power	215 W	215 W
Nominal output current	1.1 A (A rms at nominal duration)	0.9 A (A rms at nominal duration)
Nominal voltage/range	208 V / 183-229 V	240 V / 211-264 V
Nominal frequency/range	60.0 / 57-61 Hz	60.0 / 57-61 Hz
Extended frequency range*	57-62.5 Hz	57-62.5 Hz
Power factor	>0.95	>0.95
Maximum units per 20 A branch circuit	25 (three phase)	17 (single phase)
Maximum output fault current	850 mA rms for 6 cycles	850 mA rms for 6 cycles
EFFICIENCY		
CEC weighted efficiency, 240 VAC	96.5%	
CEC weighted efficiency, 208 VAC	96.5%	
Peak inverter efficiency	96.5%	
Static MPPT efficiency (weighted, reference EN50530)	99.4 %	
Night time power consumption	65 mW max	
MECHANICAL DATA		
Ambient temperature range	-40°C to +65°C	
Dimensions (WxHxD)	171 mm x 173 mm x 30 mm (without mounting bracket)	
Weight	1.6 kg (3.4 lbs)	
Cooling	Natural convection - No fans	
Enclosure environmental rating	Outdoor - NEMA 6	
FEATURES		
Compatibility	Compatible with 60-cell PV modules.	
Communication	Power line	
Integrated ground	The DC circuit meets the requirements for ungrounded PV arrays in NEC 690.35. Equipment ground is provided in the Engage Cable. No additional GEC or ground is required. Ground fault protection (GFP) is integrated into the microinverter.	
Monitoring	Enlighten Manager and MyEnlighten monitoring options	
Compliance	UL1741/IEEE1547, FCC Part 15 Class B, CAN/CSA-C22.2 NO. 0-M91, 0.4-04, and 107.1-01	

\* Frequency ranges can be extended beyond nominal if required by the utility

To learn more about Enphase Microinverter technology, visit [enphase.com](http://enphase.com)



© 2014 Enphase Energy. All rights reserved. All trademarks or brands in this document are registered by their respective owner.

Now 2 Locations to serve you!



**Danville Showroom**  
730 Camino Ramon, Suite 180  
RoseGarden Center  
Danville, CA 94526



**Pleasanton Showroom**  
6700 Santa Rita Road, Suite E  
Pleasanton, CA 94588